


IIT207

IIB3022-BPKG/M/V4A/6M/WH

Inductive sensors



Made in Germany



Product characteristics

| |
|---|
| Inductive sensor |
| Metal thread M30 x 1.5 |
| Cable |
| Increased sensing range |
| Sensing range 22 mm; [nf] non-flush mountable |

Electrical data

| | |
|-----------------------------|-------------|
| Electrical design | DC PNP |
| Operating voltage [V] | 10...36 DC |
| Current consumption [mA] | < 10 (24 V) |
| Protection class | II |
| Reverse polarity protection | yes |

Outputs

| | |
|--------------------------|---------------|
| Output function | normally open |
| Voltage drop [V] | < 2.5 |
| Leakage current [mA] | < 0.5 |
| Current rating [mA] | 100 |
| Short-circuit protection | pulsed |
| Overload protection | yes |
| Switching frequency [Hz] | 100 |

Range

| | |
|------------------------------|-----------|
| Sensing range [mm] | 22 |
| Real sensing range (Sr) [mm] | 22 ± 10 % |
| Operating distance [mm] | 0...17.82 |

Accuracy / deviations

| | |
|------------------------------|--|
| Correction factors | mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / Al approx. 0.4 / Cu approx. 0.3 |
| Hysteresis [% of Sr] | 3...15 |
| Switch-point drift [% of Sr] | -10...10 |

Environment

| | |
|--------------------------|----------------|
| Ambient temperature [°C] | 0...100 |
| Protection | IP 68 / IP 69K |

Tests / approvals

| | |
|-----|--|
| EMC | EN 61000-4-2 ESD: 4 kV CD / 8 kV AD |
| | EN 61000-4-3 HF radiated: 10 V/m (80...1000 MHz) |
| | EN 61000-4-4 Burst: 2 kV |
| | EN 61000-4-6 HF conducted: 10 V (0.15...80 MHz) |
| | EN 55011: class B |

IIT207

IIB3022-BPKG/M/V4A/6M/WH

Inductive sensors

| | | |
|------|---------|------|
| MTTF | [Years] | 1594 |
|------|---------|------|

Mechanical data

| | | |
|-------------------|--|-------|
| Mounting | non-flush mountable | |
| Housing materials | stainless steel (316L); active face: PEEK (polyether ether ketone) | |
| Weight | [kg] | 0.321 |

Displays / operating elements

| | | |
|--------------------------|-----|------------------|
| Output status indication | LED | yellow (4 x 90°) |
|--------------------------|-----|------------------|


Electrical connection

| | | |
|------------|---|--|
| Connection | PVC cable / 6 m; 3 x 0.34 mm ² | |
|------------|---|--|

Wiring

Core colours

| | |
|----|-------|
| BK | black |
| BN | brown |
| BU | blue |



Accessories

| | | |
|------------------------|-------------|--|
| Accessories (included) | 2 lock nuts | |
|------------------------|-------------|--|

Remarks

| | | |
|---------------|---------|---|
| Pack quantity | [piece] | 1 |
|---------------|---------|---|