


O6E304

O6E-FNKG

Photoelectric sensors



- 1: output function switch
2: potentiometer sensitivity

Made in Germany



Product characteristics

Through-beam sensor

Rectangular Metal

Cable

adjustable

Receiver

Sensing range 10m

Electrical data

Electrical design	DC NPN
Operating voltage [V]	10...30 DC
Current consumption [mA]	20 (24 V)
Type of light	Red light 633 nm
Protection class	III
Reverse polarity protection	yes

Outputs

Output function	light-on/dark-on mode selectable
Voltage drop [V]	< 2.5
Current rating [mA]	100
Short-circuit protection	pulsed
Switching frequency [Hz]	1000

Range

Sensing range [m]	10
-------------------	----

Excess gain graphs


x: distance in [mm]

y: excess gain factor

O6E304

O6E-FNKG

Photoelectric sensors



Environment

Ambient temperature	[°C]	-25...80
Protection		IP 65 / IP 67 ; IP 68 / IP 69K

Tests / approvals

EMC		EN 60947-5-2
MTTF	[Years]	1014
UL approval number		E003

Mechanical data

Housing materials		housing: stainless steel 316L / 1.4404; plastics: PPSU
Lens material		PMMA
Weight	[kg]	0.036

Displays / operating elements

Output status indication	LED	yellow
Operation	LED	green

Electrical connection

Connection		PVC cable / 2 m; 3 x 0.25 mm²
------------	--	-------------------------------


Wiring

Core colours

BN brown

BK black

BU blue



Remarks

Remarks		UL - Class 2 source required
Pack quantity	[piece]	1