


OIH282

OIH-HNKG/US/600MM

Photoelectric sensors



Made in USA



Product characteristics

Diffuse reflection sensor	
Connector	
Background suppression	
Range 600mm (Range referred to white paper 200 x 200 mm, 90 % remission)	

Electrical data

Electrical design	DC NPN
Operating voltage [V]	10...30 DC; "supply class 2" to cULus.
Current consumption [mA]	35
Type of light	red light 625 nm
Protection class	III
Reverse polarity protection	yes


Outputs

Output function	light-on mode
Voltage drop [V]	< 2.5
Current rating [mA]	200
Short-circuit protection	pulsed
Overload protection	yes
Switching frequency [Hz]	300

Range

Range [mm]	600 (Range referred to white paper 200 x 200 mm, 90 % remission)
Light spot diameter [mm]	30 (at maximum range)

Accuracy graph




- a: sensor
- b: object
- c: background
- x: distance sensor / object
- y: min. distance object / background

OIH282

OIH-HNKG/US/600MM

Photoelectric sensors



Values in [mm]

1 = object black (6 % remission), background white (90 % remission)

2 = object grey (18 % remission), background white (90 % remission)

3 = object white (90 % remission), background white (90 % remission)

Environment

Ambient temperature	[°C]	-25...60
Protection		IP 67

Tests / approvals

EMC		EN 60947-5-2
-----	--	--------------

Mechanical data


Housing materials		Zinc Alloy nickel-plated
Lens material		PMMA

Displays / operating elements

Output status indication	LED	yellow
Operation	LED	green

Electrical connection

Connection		M12 connector
------------	--	---------------

Wiring

Accessories

Accessories (included)		1 lock nut
------------------------	--	------------

Remarks

Pack quantity	[piece]	1
---------------	---------	---