


OY010S

OYA1510-14-4-06-P-1

Photoelectric sensors

Please note the wiring of the sensor and the sockets (see data sheet) as for 8-pole sockets the core colours are not standardised.



T: Transmitter

R: Receiver

1: LED 3 colours (red/green/orange)

2: LED 2 colours (yellow/blue)

3: LED 2 colours (red/green)



Product characteristics

Safety light curtain

Length L: 1563 mm

Connector

Complies with the requirements:

type 4 (IEC 61496-1)

SIL 3 (IEC 61508)

SILcl 3 (IEC 62061)

PL e (EN ISO 13849-1)

Electrical data

Electrical design		DC PNP
Operating voltage	[V]	24 DC (19.2...28.8)
Current consumption		
- Transmitter	[mA]	42
- Receiver	[mA]	83
Type of light		Infrared light 950 nm
Protection class		III
Reverse polarity protection		yes
Power-on delay time	[s]	< 2

Outputs

OY010S

OYA1510-14-4-06-P-1

Photoelectric sensors

Outputs (OSSDs)	2 x PNP
Max. current load per output [mA]	400 (24 V)
Short-circuit protection	yes

Range	
Protected area height [mm]	1510
Resolution (detection capacity d)[mm]	14
Protected area width (range) [m]	0...3 / 1...6

Reaction times	
Response time [ms]	20

Environment	
Applications	Class C to EN 60654-1 weatherproof application
Ambient temperature [°C]	-10...55
Max. relative air humidity [%]	95
Protection	IP 65 / IP 67

Tests / approvals	
EMC	IEC 61496-1
Shock resistance	IEC 61496-1
Vibration resistance	IEC 61496-1

Safety classification	
Mission time TM [h]	175200
Test interval T1 [Years]	20
Safety-related reliability PFHd [1/h]	3.2E-08
MTTFd [Years]	100
DC/CCF/Cat.	92.9 % / 80 % / 4



Mechanical data	
Length L [mm]	1563
Housing materials	housing: aluminium; window: PC
Weight [kg]	6.155

Displays / operating elements	
Display	LED yellow LED green LED Red LED blue LED orange

Electrical connection

Transmitter	
Connection	M12 connector

Wiring Transmitter




Receiver	
Connection	M12 connector

OY010S

OYA1510-14-4-06-P-1

Photoelectric sensors

Wiring Receiver



Max. connection cable length	[m]	100 *)
Accessories		
Accessories (included)	6 Mounting angle; 6 Mounting Nuts; nuts	
Remarks		
Remarks	*) for wire cross-section 0.34 mm²	
Pack quantity	[piece]	1

ifm electronic gmbh • Friedrichstraße 1 • 45128 Essen — We reserve the right to make technical alterations without prior notice. — GB — OY010S — 03.09.2010

Please note the wiring of the sensor and the sockets (see data sheet) as for 8-pole sockets the core colours are not standardised.