


GG711S

GIGA4008-2PS/SIL2/V4A/US

Inductive sensors



Made in Germany



Product characteristics

Fail-safe inductive sensor

Metal thread M18 x 1

M12 connector

Enable zone 1...8 mm; [nf] non-flush mountable

Complies with the requirements:

EN ISO 13849-1: 2008 category 2 PL d

IEC 61508: SIL 2

IEC 62061: SILcl 2

Application

Type of operation	continuous operation (maintenance-free)
-------------------	---

Electrical data

Electrical design	DC PNP
Operating voltage [V]	24 DC (19.2...30 DC)
Rated insulation voltage [V]	30
Current consumption [mA]	< 30
Protection class	III
Reverse polarity protection	yes
Power-on delay time [s]	1

Outputs

Output function	2 x OSSD (A1 and A2)
Output voltage at 24 V	compatible with EN 61131-2 inputs type 1, 2
Voltage drop [V]	< 2.5; (30 mA)
Current rating [mA]	100
Short-circuit protection	yes

Range

Enable zone [mm]	1...8
Safe switching off distance s(ar)[mm]	12


Reaction times

Response time to safety request [ms]	≤ 1
Response time when approaching the enable zone (enable time) [ms]	≤ 1
Risk time (response time for safety-related faults) [ms]	≤ 20

GG711S

GIGA4008-2PS/SIL2/V4A/US

Inductive sensors

Environment	
Applications	Class C to EN 60654-1 weatherproof application
Ambient temperature [°C]	-25...70, for service life ≤ 87600 h 10...40, for service life ≤ 175200 h
Rate of temperature change [K/min]	0.5
Max. relative air humidity [%]	5...95, briefly 5...70, permanently
Air pressure [kPa]	80...106
Height above sea level [m]	≤ 2000
Ionising radiation	not permissible
Salt spray	no
Protection	IP 65 / IP 67
Tests / approvals	
EMC	IEC 60947-5-2
Shock resistance	IEC 60947-5-2
Vibration resistance	IEC 60947-5-2
Safety classification	
Mission time TM [h]	≤ 175200, (20 years)
Safety-related reliability PFHd [1/h]	1.0E-07
MTTFd [Years]	2011
DC/CCF/Cat.	87 % / 70 % / 2
Mechanical data	
Mounting	non-flush mountable
Housing materials	stainless steel 316Ti / 1.4571; PBT
Weight [kg]	0.136
Displays / operating elements	
Display	LED yellow (signal), LED green (power)
Electrical connection	
Connection	M12 connector; Gold-plated contacts
Wiring  1: Safety-related logic unit	
Accessories	
Accessories (included)	2 lock nuts
Remarks	
Remarks	Unless stated otherwise, all data refer to the 24x24x1 mm reference target plate to IEC 60947-5-2 (FE360 = mild steel) over the whole temperature range.
Pack quantity [piece]	1