


ME5010

MEK3060-BPKG/AS-514-TPS

Magnetic sensors, cylinder sensors



Made in Germany

Product characteristics

Magnetic sensor

Metal thread M8 x 1

Connector

Sensing range 60 mm; referred to magnet M4.0

Magnetic sensitivity ca. 1.2 mT

Electrical data

Electrical design	DC PNP
Operating voltage [V]	10...30 DC; "supply class 2" to cULus.
Current consumption [mA]	< 10
Protection class	III
Reverse polarity protection	yes

Outputs

Output function	normally open
Voltage drop [V]	< 2.5
Current rating [mA]	200
Short-circuit protection	pulsed
Overload protection	yes
Switching frequency [Hz]	5000

Range

Sensing range [mm]	60, referred to magnet M4.0
Magnetic sensitivity [mT]	ca. 1.2

Accuracy / deviations

Hysteresis [% of Sr]	1...10
----------------------	--------

Environment

Ambient temperature [°C]	-25...75
Protection	IP 67

Tests / approvals

EMC	EN 61000-4-2 ESD: 4 kV CD / 8 kV AD EN 61000-4-3 HF radiated: 10 V/m (80...1000 MHz) EN 61000-4-4 Burst: 2 kV EN 61000-4-5 Surge: 0.5 kV (line to line, Ri: 20Ω) EN 61000-4-6 HF conducted: 10 V (0.15...80 MHz) EN 55011: class B
MTTF [Years]	2935

Mechanical data

Housing materials	housing: stainless steel (316L); active face: PBT orange
Weight [kg]	0.027

Displays / operating elements

ME5010

MEK3060-BPKG/AS-514-TPS


Magnetic sensors, cylinder sensors

Output status indication	LED	yellow
--------------------------	-----	--------

Electrical connection

Connection	M8 connector; Gold-plated contacts
------------	------------------------------------

Wiring



Accessories

Accessories (included)	2 lock nuts
------------------------	-------------

Remarks

Pack quantity	[piece]	1
---------------	---------	---